



PARAMÈTRES

- **Pixel Pitch** : 8.3mm
- **LED Type** : 3-in-1 SMD
- **LED Configuration** : 1Red,1Green,1Blue
- **Brightness** : 4500-5000cd/m²
- **Pixel Density** : 14,400 pixels/m²
- **Pixels Per Panel** : 96×96 Dots
- **Module Size** : W400mm×H200mm
- **Cabinet Size** : W800mm×H800mm×D87mm
- **Aspect ratio** : 1:1
- **Weight** : 15.7 kg/panel
- **Area** : 0.64 m²
- **Recommended Viewing Distance** : ≥8.3 m
- **Material** : Die-cast Magnesium
- **Transparency** : 12%
- **Environment** : Outdoor
- **Ingress Protection** : IP65/IP54
- **Operating Temperature/Humidity** : -20C°~+50C°/10~90C°RH
- **Storage Temperature/Humidity** : -30C°~+60C°/10~95C°RH
- **Maintenance** : Rear
- **Horizontal Viewing** : Angle 140°
- **Vertical Viewing** : Angle 140°
- **Color Temperature** : 2000K~9300K Adjustable
- **Calibration Support** : brightness and chroma
- **Brightness Control** : Manual/Automatic
- **Input Power <Max>** : 400W/panel
- **Input Power <Typical>** : 140 W/panel
- **Driving Method** : Constant Current Drive
- **Video Frame Rate** : 50/60Hz
- **Rate Refresh** : 1920Hz
- **Input Voltage** : 100~240VAC
- **Input Power Frequency** : 50~60Hz
- **Input Signal** : DVI/HDMI/VGA/SDI/DP/AV/S-Video, etc
- **LED Life Time** : ≥100,000 Hours
- **LED Wavelength** : R:620~630nm G:520~535nm B:465~475nm
- **Standard Mounting Configuration** : Floor-mounted, Hanged
- **Professional Services** : Design, configuration, install and service available
- **Data Interconnection** : Network Cable (L≤100m);
multi-mode fiber (L≤300m); single mode fiber (L≤15km)

87mm

