




POWERLEDZOOM

BY KINESIK



PARAMÈTRES

- **Light Source:** 4 LEDs (quad- color RGBW) 10W, (700mA)
- **Zoom Angle:** 8° to 40°
- **Max.Flx (8°) :** 560.17 lm
- **Peak Intensity (8°) :** 21676 cd
- **Illuminance (8°):** 750 lux @ 5m
- **Illuminance (40°):** 70 lux @ 5m
- **Selectable PWM:** 600/1200/2400/4000 Hz
- **Dimmer :** Electronic
- **Shutter/Strobe :** Electronic
- **Zoom :** Motorized
- **Strobe Rate :** 0 to 20 Hz
- **Color Temperature Presets :** 2500 - 10000K
- **Standalone Color Mixing**
- **Automated Programs**
- **Customizable Programs**
- **Dim Modes :** 2 Built-in
- **Control Protocol:** DMX512, W-DMX
- **DMX Channels:** 6/9/12
- **4 Button Control Panel**
- **TFT Menu Display**
- **Dimensions :** 240x191x286 mm (9.45 x 7.52 x 11.26 in)
- **Weight :** 6 kg (13.23 lb)
- **Exterior Color:** Black
- **Housing Material :** Die-cast aluminum
- **Cooling:** Natural cooling
- **Power Input :** Seetronic PowerCON IP65
- **Data Connectors :** 3-pin IP65 XLR
- **Cable Length (power) :** 1.2 m (3.9ft)
- **Duration 8 hours full white,**
- **20 hours color fade**
- **7-hour fast charge from flight case,**
- **9 hours in slow charge with PowerCon**
- **More than 1,000 charge/deplete cycles**
- **Standard Voltage:** 18.5V
- **Standard Capacity:** 15.4Ah
- **Rated Power:** 284.9Wh
- **Li-ion battery**
- **No acid leaks**
- **Input Voltage:** 100 to 240 VAC, 50/60 Hz (auto-ranging)
- **Power and Current (120V/60Hz) :** 45.1W, 0.665A
- **Power and Current (240V/50Hz) :** 45.2W, 0.398A
- **IP Rating:** IP65, outdoor/wet
- **Operation Temperature:** -20°C ~ 40°C



Product Overview

